

1  
2  
3  
4  
5  
6  
7  
8  
9  
0  
1  
2  
3  
4  
5  
6  
7  
8  
9  
0  
1  
2  
3

2

## 3

## 4

## 5

- 6  
7  
8  
9  
0  
1  
2  
3  
4  
5  
6  
7  
8  
9  
0  
1  
2  
3

1 that function as position detector to generate position signals to indicate the position of said  
2 read/write heads relative to said surface of said disk, and

3 g. two flexible printed circuit (FPC) boards that have the wiring board connections  
4 which have signal lines that connect said magnetic heads and the actuators to the drive  
5 electronics board via the connection and moving members.

6 h. two analog voice coil motors that move the said wing shaped two pairs of  
7 actuators along two different-independent stationary linear paths of micro-rails,  
8 and;

9 i. said analog voice coil motors also have a digital mode-switching from analog to  
10 digital mode and back to analog-for skipping data tracks-when micro actuation is  
11 not needed.

12  
13 2. (Original) The positioning and actuator-carriage arm system as set forth in claim 1,  
14 includes two wing shaped pairs of actuators; where each pair moves in unison-parallel to  
15 each other.

16  
17 3. (Original) The actuator-carriage arm and suspension system as recited in claim 2, wherein  
18 said two pairs of actuators that move within their limited range-enable; the distance that each  
19 actuator member of these pairs have to cover to be a considerably shorter distance to reach  
20 different concentric tracks of the disk.

21  
22 4. (Original) The actuator-carriage arm system as recited in claim 3, wherein said two pairs  
23 of actuators that are assigned to move only within a limited range, this said distance of back

1 and forth motion is limited for each member to only 1/2 of the distance of the radius of the  
2 disk-excluding the non data zone-during operation, thereby; increases each members  
3 precision, enables several layers of programs to be loaded faster at boot up, and speeds up the  
4 external transfer rate and shortens the overall access-retrieval time of said drive.

5  
6 5. (Original) The actuator-carriage arm and suspension system as recited in claim 2, wherein  
7 the two pairs of wing shaped actuators and the series of multiple R/W heads enable sufficient  
8 excess number of R/W transducer heads; that can access a multitude of data tracks with  
9 precision that are close or adjacent and therefore an additional built in micro actuator is not  
10 needed and thereby the cost of integrating micro actuator is avoided.

11  
12 6. (Original) The actuator-carriage arm and suspension system as set forth in claim 1,  
13 wherein said member wing shaped actuators are arranged; to move over two different  
14 quadrants of the disk area concurrently.

15  
16 7. (Original) The actuator-carriage arm and suspension system as recited in claim 5, wherein  
17 said wing shaped actuators and the R/W heads of said second pair of actuators that are  
18 affixed to said integrated suspension of said second actuators, can have access to same set of  
19 multiple tracks; with only 1/2 revolution of the disk, when actuators are positioned  
20 symmetrically over same set of tracks and over the opposite quadrants of the disk.

21  
22 8. (Original) The actuator and carriage arm and suspension system as set forth in claim 1,  
23 wherein the movement of each other pair of wing shaped actuator; is independent of the

1 movements of the other pair of actuator.

2  
3 9. (Original) The actuator-carriage arm and suspension system as recited in claim 7, wherein  
4 the said actuators, if not positioned symmetrically, a multitude of different set of tracks are  
5 accessed by the said R/W heads of the said actuators that are in an asymmetric position; with  
6 only less than one revolution of the disk.

7  
8 10. (Currently Amended) The actuator-carriage arm system as set forth in claim 1, wherein  
9 a total of ~~two hundred and seventy two~~ twenty four thin film R/W heads and ~~one hundred and~~  
10 ~~thirty six~~ twelve (one micro-pad for two R/W heads,) or -multiples thereof- micro-pads are  
11 affixed to ~~the~~ each of the wing shaped actuator-carriage arms, wherein each actuator covers  
12 ~~17 multiple~~ tracks concurrently ~~and there are four evenly interspaced transducers for each~~  
13 ~~track thereby each member actuator of the pairs; has access in increments of one hundred~~  
14 ~~and forty seven tracks per 1/2 concentric limited range assigned -where concurrent R/W does~~  
15 not have to be made using all of R/W heads at the same time and in another mode R/W is  
16 done sequentially, even as actuators remain stationary over a set of certain tracks or make  
17 micro distance re-positioning.

18  
19 11. (Original) The actuator-carriage arm and integrated suspension system as recited in  
20 claim 7 and 9, wherein the arc like shaped geometry and plurality of wing shape of the  
21 actuator and the double pair configuration of said actuator arms and a series of R/W heads  
22 form an arc like path and two wings extend over and conform to the arcs of the data tracks  
23 below, thereby; enable an uninterrupted row of complete disk sectors to pass under these said

1 R/W head members, as said R/W heads do not need to be re-positioned frequently-as in the  
2 prior art, and therefore enable a parallel data transfer scheme.

3  
4 12. (Original) The actuator-carriage arm and suspension system as set forth in claim 1,  
5 wherein both pairs of the actuators and their R/W heads are connected to the drive electronics  
6 board, by flexible printed circuit (FPC) board electronic wiring connection that connects  
7 actuators and R/W heads to the drive electronics board, via the member that moves the pair  
8 of actuator.

9  
10 13. (Original) The actuator-carriage arm and integrated suspension system as recited in  
11 claim 12, wherein; the electronic communication between actuators and R/W heads can  
12 alternatively be established with a micro-range Blue tooth technology instead of flexible  
13 printed circuit wiring.

14  
15 14. (Original) The actuator-carriage arm and suspension system as set forth in claim 1,  
16 wherein the two stationary micro-rails per disk surface, facilitate linear movements of said  
17 member wing shaped actuators, that enable the R/W transducer heads of said integrated  
18 suspensions of said actuators to have a continuous contact pad and a constant fly height; that  
19 enables a unique parking feature of the heads, where the R/W heads that are affixed on the  
20 wing shaped actuator and integrated two suspension sides move within the two limited 1/2  
21 inner range of the radius of the disk, are moved to positions-over two concentrically aligned  
22 non data zones-which are concentric rings-one located at the outer diameter-the other closer  
23 to center of the disk, thereby;

1 a) system is not subject to contact start stop (CSS) operation method and,  
2 b) system is not subject to Quasi-Rigid body vibrations and relatively high vibrations  
3 due to frequent direction reversals during the boot up, scandisk, defragmentation,  
4 compression, backup and maintenance tasks-and any other tasks that involve having to reach  
5 the entire or most or data tracks that are located in different parts of the disk area.  
6

7 15. (Original) The actuator-carriage arm and integrated suspension system as recited in  
8 claim 14, wherein the low fly height, is in the order of 0.1-0.5 micron above the disk surface.  
9

10 16. (Original) The actuator-carriage arm and suspension system as set forth in claim 1,  
11 wherein the disk members have an optimal rpm of 7200 rpm in order to avoid heating.  
12

13 17. (Original) The actuator-carriage arm system as set forth in claim 1, wherein the actuator  
14 arms and suspensions with multiple R/W heads, have embedded servo write-detection  
15 member heads to enable precise positioning on the disk  
16

17 18. (Original) The actuator-carriage arm and suspension system as set forth in claim 1,  
18 wherein the magnetic disk members that are used to write and read information upon, have a  
19 protective wear-resistant coating-that is compatible to the micro pads-that protects the  
20 magnetic layer and creates a smooth but textured surface with low capillary adhesion-and  
21 make R/W heads-independent of air lifting of disk tangential velocity.  
22

23 19. (Original) The actuator-carriage arm and integrated system as recited in claim 18,

1 wherein the independence from air lifting of disk tangential velocity is mainly a combination  
2 of functions of the continuous contact of micro-pads, and the constant height feature provided  
3 by the stationary micro-rail.  
4

5 20. (Original) The actuator-carriage arm and suspension system as recited in claim 18,  
6 wherein the protective wear-resistant layer is preferably titanium di-boride or amorphous  
7 nitrided carbon, or chromium, or tungsten and the disk surface has an adhesion reducing  
8 texture.  
9  
10  
11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23